



SUNITRON INC.[®]

40 Pippin Rd., Bldg. # 4, Concord, On. L4K 4M6 Canada


Tel: (905) 660-6888 Fax: (905) 660-8889 Toll Free: 877-630-8811

Indoor - Outdoor Computerized LED Sign Since 1986

Visit us at... www.sunitron.com

MegaStar II -250 / 1

- ⇒ Standard 16 mm Pitch 4.5" character.
- ⇒ Indoor / Outdoor Applications
- ⇒ High resolution (144x7 pixel)
- ⇒ LED(s) x Pixel: 2
- ⇒ Number of Lines: 1
- ⇒ Characters x Line: 24 (@7x5 Font)
- ⇒ Cabinet Dimension: 96" x 11" x 6"
- ⇒ Character Height (Small): 4.5"
- ⇒ Full matrix display
- ⇒ Superbright daylight visibility
- ⇒ Multistage light sensor (power saver)
- ⇒ Number of LED's: 2016 LED's
- ⇒ Max. Power consumption: 109 Watts
- ⇒ Viewing angle: 90°
- ⇒ Display Area: 91" x 4.5"
- ⇒ Character Height (Large): 4.5"



A Business With A Good Sign - is A Sign of A Good Business[®]



SUNITRON INC.[®]

40 Pippin Rd., Bldg. # 4, Concord, On. L4K 4M6 Canada

Tel: (905) 660-6888 Fax: (905) 660-8889 Toll Free: 877-630-8811

Indoor - Outdoor Computerized LED Sign Since 1986

Visit us at... www.sunitron.com

Technical Specifications MegaStar Series Outdoor Display

Description Module:	256mm x 128mm Approx.(10"x5") Double sided Treated PCB outdoor use.
No. LED's x Pixel:	Two Superbright Red or Yellow Diodes (LED's).
Pixel Pitch:	Center to center spacing: 16mm or .63".
Viewing angle:	90 degree's.
Controller:	Static bias driver .
Brightness:	1000 mcd per @ LED.
Power consumption:	0.108 watts per pixel maximum high power efficiency.
Estimated lifetime:	LED manufacturer estimates diode life expectancy at 100,000 hours at 30° C Sunitron Inc. will warranty diodes for our standard warranty policy period 1year.
Construction:	Steel cabinet black plastic coated with 6.35 mm louvers front face.
Cooling System:	Automatic on /off (forced air fan).
Display matrix:	8 x 16 per modules of 2 LED's per pixel Modules are designed to be "snapped" in and out for quick service.
Features:	Time, Date and Temperature.
Communication: PC to Sign	Via hardwire (RS232 or RS422) up to 4000 ft. Modems requires telephone line on site Wire-less communication. Operable in TCP/IC for Netware Connectivity
Automatic Dimmer:	Multi-stage light sensor "Power Saver" .
Warranty:	1-year service depot warranty on all parts and labour, including on line direct support toll free # 1-877-630-8811.
Technical Support:	Five year technical support for software upgrading.
Operation Software:	To run under Micro-soft Windows 9x/XP environment.
Power requirement:	110/120Vac service, internal switch powers supply 7.5 Vdc. With automatic circuit for over voltage protection shot-/off.
Electrical cable:	To be determinate by electrical contractor according to CSA standard.

A Business With A Good Sign - is A Sign of A Good Business[®]